

2.06 PRIMAFLEX PVC SUPER M

Temperature range 0 °C bis 70 °C



Description

Light to medium heavy, flexible PVC flex hose. Made of elastic PVC with inside, sheathed spring steel spiral.

Suitable for the passage of air, gases, vapours and liquids.

Available in our online shop

Properties

- Flexible
- Light
- Elastic
- Largely smooth interior
- Wall thickness: 0.50 – 0.60 mm

Application ranges

Ventilation, Ventilation, Dust removal, Suction technology, PVC hoses, Exhaust air systems, Suction hoses, dusts and powder, Suction hoses, air and gaseous media, Plant engineering, Roof ventilation, Elastic hose, highly, Blower hose, Air-conditioning and ventilation technology, Fan hose, Ventilation technology, Dust suction

Length

Standard length: 10 m.

Further informations

Standard color: grey, but also available in black or transparent.

Special colors: other RAL colors upon request.

TECHNICAL SPECIFICATIONS

| Inner-Ø (mm) | Outer-Ø (mm) | Bending radius (mm) | Pressure (bar) | Vacuum (bar) | Weight (kg/m) | Length (m) | Article-No. |
|--------------|--------------|---------------------|----------------|--------------|---------------|------------|-------------|
| 25 | 31 | 25 | 1,6 | 0,18 | 0,32 | 10 | 2032025 |
| 28 | 34 | 28 | 1,5 | 0,18 | 0,358 | 10 | 2032028 |
| 32 | 38 | 32 | 1,4 | 0,18 | 0,4 | 10 | 2032032 |
| 35 | 41 | 35 | 1,3 | 0,18 | 0,448 | 10 | 2032035 |
| 38 | 44 | 38 | 1,3 | 0,18 | 0,48 | 10 | 2032038 |
| 41 | 47 | 41 | 1,3 | 0,16 | 0,525 | 10 | 2032041 |
| 44 | 50 | 44 | 1,2 | 0,14 | 0,563 | 10 | 2032044 |
| 51 | 57 | 51 | 1,2 | 0,13 | 0,652 | 10 | 2032051 |
| 63 | 69 | 32 | 0,9 | 0,12 | 0,806 | 10 | 2032063 |
| 70 | 76 | 70 | 0,8 | 0,1 | 0,896 | 10 | 2032070 |
| 76 | 82 | 76 | 0,7 | 0,08 | 0,972 | 10 | 2032076 |
| 80 | 86 | 80 | 0,6 | 0,07 | 1,024 | 10 | 2032080 |
| 89 | 95 | 89 | 0,6 | 0,07 | 1,139 | 10 | 2032089 |
| 102 | 108 | 102 | 0,5 | 0,06 | 1,306 | 10 | 2032102 |