

2.06 PRIMAFLEX PVC SUPER M

Temperature range 0 °C bis 70 °C



Description

Light to medium heavy, flexible PVC flex hose. Made of elastic PVC with inside, sheathed spring steel spiral.

Suitable for the passage of air, gases, vapours and liquids.

Available in our online shop

Properties

- Flexible
- Light
- Elastic
- Largely smooth interior
- Wall thickness: 0.50 – 0.60 mm

Application ranges

Ventilation, Ventilation, Dust removal, Suction technology, PVC hoses, Exhaust air systems, Suction hoses, dusts and powder, Suction hoses, air and gaseous media, Plant engineering, Roof ventilation, Elastic hose, highly, Blower hose, Air-conditioning and ventilation technology, Fan hose, Ventilation technology, Dust suction

Length

Standard length: 10 m.

Further informations

Standard color: grey, but also available in black or transparent.

Special colors: other RAL colors upon request.

TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Outer-Ø (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Price (€/m)	Article-No.
25	31	25	1,6	0,18	0,32	10	3,52 €	2032025
28	34	28	1,5	0,18	0,358	10	3,62 €	2032028
32	38	32	1,4	0,18	0,4	10	3,47 €	2032032
35	41	35	1,3	0,18	0,448	10	3,94 €	2032035
38	44	38	1,3	0,18	0,48	10	4,08 €	2032038
41	47	41	1,3	0,16	0,525	10	4,22 €	2032041
44	50	44	1,2	0,14	0,563	10	4,36 €	2032044
51	57	51	1,2	0,13	0,652	10	4,80 €	2032051
63	69	32	0,9	0,12	0,806	10	5,37 €	2032063
70	76	70	0,8	0,1	0,896	10	5,71 €	2032070
76	82	76	0,7	0,08	0,972	10	7,45 €	2032076
80	86	80	0,6	0,07	1,024	10	7,69 €	2032080
89	95	89	0,6	0,07	1,139	10	8,21 €	2032089
102	108	102	0,5	0,06	1,306	10	8,97 €	2032102