


## 4.08 PRIMAFLEX SPIRA PRO FIREFLEX

Temperature range -20 °C bis 150 °C



### Description

Very lightweight, very flexible PVC-free hot air hose, heating unit hose, fan hose, spiral hose. Up to +150°C Flame retardant according to EN13 501 B-s1-d0.

For the medium temperature range made of PU-coated polyester fabric and outside with a galvanically galvanized spring steel spiral incorporated under a scratch protection. Handcrafted with special know-how high-end product made of high-quality raw material.

Excellent for conveying cold or hot air to mobile heaters.

For tent air conditioning, building heating, event ventilation.

Available in our online shop

### Properties

- PVC-free
- odourless
- Flame-retardant according to EN13501 B-s1-d0
- Lightweight
- Highly flexible
- High tensile strength
- Non-kniking
- High compressibility
- With scuff protection
- Large diameters available
- Continuous connection possible
- Spiral-free sleeves

### Application ranges

Construction site heating, Drying of buildings, Drying buildings, Drying grain, Blower hose, Hot air, Heating fans, Hay blowers, Fan hose, Air-conditioning and ventilation technology, Drying Technology, Hot air hoses, Wind generator plants, Shipyards, Ventilation, Ventilation, Tent heating, Tent air-conditioning,

### Length

Standard length: 7,6 m. Other lengths on request.

### Further informations

Also available upon request as spiral-free or insulated flat hose.

For increased vacuum conditions also tailor-made narrower spiral slopes can be produced.

Also welded types available.

Color: yellow-black, white-black, grey-black.

Extras: end rings instead of end sleeves, hooks or eyelets for suspended installation.

# TECHNICAL SPECIFICATIONS

Inner-Ø (mm)	Spiral spacing (mm)	Bending radius (mm)	Pressure (bar)	Vacuum (bar)	Weight (kg/m)	Length (m)	Price (€/m)	Article-No.
102	50	50	0,3	0,035	0,25	7,6	27,90 €	Specification after color choice
127	75	63	0,3	0,035	0,313	7,6	23,84 €	
152	100	76	0,3	0,035	0,4	7,6	15,58 €	
203	125	102	0,275	0,035	0,53	7,6	20,64 €	
229	150	114	0,25	0,021	0,61	7,6	23,21 €	
254	175	127	0,225	0,021	0,66	7,6	26,09 €	
305	225	153	0,175	0,021	0,8	7,6	22,51 €	
356	225	178	0,15	0,021	0,93	7,6	26,19 €	
407	225	204	0,125	0,021	1,06	7,6	29,88 €	
425	225	213	0,12	0,021	1,13	7,6	31,17 €	
457	225	229	0,11	0,021	1,19	7,6	33,48 €	
508	225	254	0,1	0,021	1,32	7,6	37,17 €	
525	225	263	0,1	0,018	1,45	7,6	38,39 €	
600	225	300	0,085	0,014	1,6	7,6	43,81 €	
700	225	350	0,7	0,01	1,87	7,6	52,44 €	
800	225	400	0,6	0,01	2,1	7,6	59,87 €	
900	225	450	0,5	0,01	2,4	7,6	67,30 €	
1000	225	500	0,4	0,01	2,67	7,6	74,65 €	